



## Indoor splitter

FUSION series

**art. 27-204**  
**CM4**

Ideal for the distribution of the TV-SAT signals in the 5÷2400 MHz frequency range.

It allows to divide the signal so that all the outputs have the same attenuation from one another.

It is an indoor product, realized in die-casting housing with screw F-type connectors.

Provided with a directional passage of current on all the outputs.

Compatible with the signals for the return line.

### Characteristics

- Realized in die-casting housing with screw F-type connectors
- Four outputs with the same attenuation from one another
- Passage of current on all the outputs



Code	27-204	
Item	CM4	
No. outputs	4	
Frequencies range	MHz	5÷2400
Tap loss TV	dB	8,5
Tap loss SAT	dB	11
Tap loss Ch.R	dB	7,5
Outputs isolation TV	dB	20
Outputs isolation SAT	dB	20
Outputs isolation Ch. R	dB	20
Return loss Ch. R	dB	12
Connectors	screw F-type	
Dimensions (LxWxH)	mm	71x35x29
Fit temperature	°C	-10 ÷ +55
Compliant to	EN 55083-2, EN 50083-4, EN 60065, EN 60728-11	

Technical data refer to a temperature of 25 °C

Packaging		
Package		multi-pack
Quantity	pcs	10
Packaging dimensions (LxWxH)	mm	184x72x65
Packaging weight	Kg	0,65

### Operation scheme

